

## LABORATORY MEDIUM FLUTER

Equipment to prepare corrugated medium paper specimens under pressure and temperature to perform standard CMT and CCT tests on a standardized crush tester.



Precise temperature control.

Rolls for standard wave A.

Distance between teeth of  $8.5 \pm 0.05$  mm.

Tooth height:  $4.75 \pm 0.05$  mm.

Rotation speed of toothed pulleys:  $4.5 \pm 1$  rpm.

Pressure between the rollers:  $100 \pm 10$  N.

### EIGENSCHAFTEN

- Precise temperature control.
- Rolls for standard wave A.
- Distance between teeth of  $8.5 \pm 0.05$  mm.
- Tooth height:  $4.75 \pm 0.05$  mm.
- Rotation speed of toothed pulleys:  $4.5 \pm 1$  rpm.
- Pressure between the rollers:  $100 \pm 10$  N.
- Adjustable Pressure Range from 0-210 N.
- Includes sample preparation device for CMT assay.
- CE marked.

### TECHNISCHE DATEN

<b>Power connection</b>	100 V / 50 Hz, 230 V / 50 Hz
<b>Compressed air connection</b>	nein
<b>PC connection</b>	No PC connection
<b>Width / Diameter</b>	48 cm
<b>Depth</b>	20 cm
<b>Height</b>	36 cm
<b>Weight (net)</b>	20 kg

### NORMEN

ISO 7263  
PAPTAC D29  
SCAN P27  
TAPPI T809