

PEEL ADHESIVE TESTING MACHINE 90°

Get precision measurements for 90° peel tests with the 90° peel adhesive testing machine. The 90° peel adhesive tester runs at varying speeds for added flexibility and offers a number of additional features.



EIGENSCHAFTEN

- Advanced digital speed control with stepper motor
- Selectable speeds of 1-24 ipm (3-60 cpm), available in even increments
- Test angle is permanently set for 90
- 10 pound load cell is included with the machine
- Capable of pulling up to 10 lbs (4.5 kg)
- Test samples as short as 1/2" to as long as 6" (12-150 mm)
- Unique design capable of testing thick samples or setups involving fixtures
- Designed to accept standard 2" x 6" peel panels (50 mm x 150 mm)
- Increments 1.25-11.25 cm/5-4.5 inches
- Operating temperature range 32°-150° F (0°-70° C)

TECHNISCHE DATEN

| | |
|----------------------------------|------------------------------|
| Power connection | 100 V / 50 Hz, 230 V / 50 Hz |
| Compressed air connection | nein |
| PC connection | USB |
| Width / Diameter | 46 cm |
| Depth | 25 cm |
| Height | 63 cm |
| Weight (net) | 20 kg |

NORMEN

| | |
|----------------|------------|
| ASTM D6252 | TLMI L-IA2 |
| PSTC-4 | TLMI L-IA3 |
| AFERA 4001 P11 | |
| ASTM D3330 | |
| FINAT FTM2 | |
| FINAT FTM11 | |
| PSTC 101 | |
| TLMI L-IA1 | |