

## ADHESION/RELEASE TESTING MACHINE

The most versatile peel tester on the market, the Adhesion/Release testing machine with digital display is designed to perform PSTC, ASTM, TLMI, FINAT, and AFERA adhesion and release testing procedures.



### EIGENSCHAFTEN

- Rugged construction, capable of withstanding the abuse of the production environment
- Digital speed control
- Selectable speed range from 1 to 1200 ipm (3-3048 cpm)
- Test angle is selectable between 90° and 180°
- One load cell is included with the machine (2, 5, 10, or 25 pound capacities available)
- Capable of pulling up to 25 lb (12 kg) (dependent on selected lower speeds)
- Accurate to +/-0.1% of load cell range
- Test samples as short as 1/2" to as long as 12" (12-305 mm)
- Operating temperature range: 32°-150° F (0°-70° C)
- Capable of stand-alone operation with integrated touch screen display

### TECHNISCHE DATEN

<b>Power connection</b>	230 V / 50 Hz
<b>Compressed air connection</b>	nein
<b>PC connection</b>	USB
<b>Width / Diameter</b>	91 cm
<b>Depth</b>	33 cm
<b>Height</b>	61 cm
<b>Weight (net)</b>	45 kg

### NORMEN

PSTC-15	FINAT FTM5
PSTC-4	FINAT FTM10
PSTC-55	FINAT FTM11
AFERA 4001 P11	PSTC 101
ASTM D3330	TLMI L-IA1
FINAT FTM1	TLMI L-IA2
FINAT FTM2	TLMI L-IA3
FINAT FTM3	