

PEEL ADHESIVE TESTING MACHINE

For added testing flexibility, the 180° peel adhesive testing machine can perform a precision 180° peel test at three different speeds. The 180° peel adhesive tester offers a number of robust features.

EZ Data - is optional: EZ Data Compatible Remote setup, operational control, and enhanced data collection are all possible when coupled with our EZ Data management software. This application requires an external PC.



options:

- Additional load cell capacities available: 2 and 5 pounds
- PSTC and TLMI testing manuals and videos
- Custom speeds

EIGENSCHAFTEN

- Rugged construction, capable of withstanding the abuse of the production environment
- Advanced digital speed control with stepper motor
- Selectable speeds of 1-24 ipm (3-60 cpm)
- Test angle is permanently set for 180° testing
- 10 pound load cell is included with the machine
- Capable of pulling up to 10 lbs (4.5 kg)
- Test samples as short as 1/2" to as long as 6" (12-150 mm)
- Designed to accept standard 2" x 6" peel panels (50 mm x 150 mm)
- Increments of 1.25 - 11.25 cm / .5-4.5 in.
- Operating temperature range 32°-122° F (0°-50° C)

TECHNISCHE DATEN

Power connection	100 V / 50 Hz, 230 V / 50 Hz
Compressed air connection	nein
PC connection	USB
Width / Diameter	58 cm
Depth	30 cm
Height	20 cm
Weight (net)	13 kg

NORMEN

PSTC-15	FINAT FTM10
PSTC-4	FINAT FTM11
PSTC-55	PSTC 101
AFERA 4001 P11	TLMI L-IA1
ASTM D3330	TLMI L-IA2
FINAT FTM1	TLMI L-IA3
FINAT FTM3	
FINAT FTM5	